

## Technical Data Sheet

# Pro 5ft. USB to RS485-RS422 Converter with FTDI Chip

Model Number: GM-485422

Rev 03.210315



Reliability and a high performance FTDI Chip puts the GM-485422 USB to RS485, RS422 serial converter at the cutting edge of serial communication. With a terminal board connector included, this small, portable, and convenient solution.

### Features

- Indication LED's for Power, TX and RX
- Plug and Play USB to RS485 Converter
- 5 feet (1.6 meter) cable. Baud rate: 300bps to 1Mbps. USB 1.1 and 2.0 compliant
- Automatic send data control Auto detection of data speed
- Built-in static and surge protection up to 600W. Terminal board included with each converter

### Product Information

- Model Number: GM-485422
- Packing List:
  -

## Specifications

### OVERVIEW

Product Type	
Electrical Protections	15KV ESD Protection
Mountable	
Material	
Compliance	N/A
LED indicators	Power, TX/RX
Requires Host to Function	

### 0

Serial Modes	RS422, RS485
RS232 Signals	
RS422 Signals	T+, T-, R+, R-, GND
RS485 2-wire Signals	T/R+, T/R-, GND
RS485 4-wire Signals	

### SERIAL SPECS

Maximum Data Rate	921.6 Kbps
Minimum Data Rate	300 baud/bps
Data Bits	
Parity	
Stop Bits	
Flow Control	
FIFO	

**Specifications Cont.****ENVIRONMENTAL**

Operating Temperature	
Operating Humidity	
Storage Temperature	

**PHYSICAL**

Length	inches
Width	inches
Height	inches
Item Weight	lbs
Ship Weight	0.8000 lbs

**OS SUPPORT**

Supported Operating Systems	Linux, OSX 10, Windows 10, Windows 8, Windows 7
-----------------------------	---

**WARRANTY**

Warranty Period	
-----------------	--

**PRODUCT URL**

GM-485422 Product Page	
------------------------	--