

Technical Data Sheet

3ft. USB 2.0 to RS-232 Serial Converter Cable w/ FTDI - Windows 10, OSX, Linux

Model Number: USA-FTDI-A36 Rev 03.210315



Windows 10 USB to serial RS232 adapter with FTDI chip is adeal for your 36 inch connection from your host USB port, the serial adapter has a 300bps to 1Mbps Baud Rate and built-in statics and electrical surge protection up to 600W.

Features

- 3ft blue USB to RS-232 serial converter cable type-A port into host, RS-232 DB-9 Male End to Female serial port
- LED activity indicators for Power, TX and RX serial signals
- FTDI Chipset Inside: FT232RL and Ultra Fast 920K ZyWyn ZT232E.
- Supported OS platforms are Windows 7, 8 and 10 as well as Linux and MacOS 10.X

•

Product Information

- Model Number: USA-FTDI-A36
- Packing List:

0



Specifications

OVERVIEW	
Product Type	Serial Adapter
Electrical Protections	15KV ESD Protection
Mountable	
Material	
Compliance	N/A
LED indicators	Power, TX/RX
Requires Host to Function	

0

Serial Modes	RS232
RS232 Signals	DCD, RxD, TxD, DTR, GND, DSR, RTS, CTS, RI
RS422 Signals	
RS485 2-wire Signals	
RS485 4-wire Signals	

SERIAL SPECS

Maximum Data Rate	460.8 Kbps
Minimum Data Rate	300 baud/bps
Data Bits	
Parity	
Stop Bits	
Flow Control	
FIFO	



Specifications Cont.

ENVIRONMENTAL	
Operating Temperature -40 to 85 C	-40 to 85 C
Operating Humidity	5% to 95% RH
Storage Temperature	-40C ~ 85C

PHYSICAL

Length	inches
Width	inches
Height	inches
Item Weight	Ibs
Ship Weight	0.1560 lbs

OS SUPPORT

Supported Operating Systems	Linux, OSX 10, Windows 10, Windows 8, Windows 7, Windows Vista, Windows XP	
-----------------------------	--	--

WARRANTY

Warranty Period

PRODUCT URL

ISA-FTDI-A36 Product Page
