

Technical Data Sheet

4-Port USB to Serial Adapter COM Retention FTDI Chipset 920K Baud Rate

Model Number: USA-FTDI4X

Rev 04.210726



Connect 4 new or additional Windows COM ports through this FTDI, the USB to serial adapter outputs are automatically configured once connected to give you an easy plug-and-play installation.

Features

- Quad Port Serial Adapter with FT4232 FTDI Chipset, that supports an automatic handshake
- This serial adapter lets you enjoy simple installation, easy plug and play USB interface options.
- Supported OS platforms are Windows 7, 8 and 10 as well as Linux and MacOS 10.X
- No power supply needed, USB interface: standard Type A female
- OS Compatibility: Windows 7, 8, and 10 as well as Linux and Mac OS 10.X

Product Information

- Model Number: USA-FTDI4X
- Packing List:
 - Driver/Software Disk, USB Serial Adapter

Specifications**OVERVIEW**

Product Type	Serial Adapter
Electrical Protections	15KV ESD Protection
Mountable	N/A
Material	Plastic
Compliance	None or N/A
LED indicators	TX/RX

SERIAL SPECS

Maximum Data Rate	921.6 Kbps
Minimum Data Rate	300 baud/bps
Data Bits	7, 8
Parity	None, Even, Odd, Mark, Space
Stop Bits	1, 2
Flow Control	
FIFO	
Serial Modes	RS232
RS232 Signals	DCD, RxD, TxD, DTR, GND, DSR, RTS, CTS, RI

Specifications Cont.**ENVIRONMENTAL**

Operating Temperature	0C ~ 55C
Operating Humidity	5% to 95% RH
Storage Temperature	-25C ~ 70C
Country of Origin	China

PHYSICAL

Ship Weight	0.53 lbs
-------------	----------

OS SUPPORT

Supported Operating Systems	Linux, OSX 10, Windows 10, Windows 8, Windows 7
-----------------------------	---

WARRANTY

Warranty Period	1 Year
-----------------	--------

PRODUCT URL

USA-FTDI4X Product Page	https://www.gearmo.com/shop/professional-4-port-rs232-usb-to-serial-adapter-gm-ftdi4x/
-------------------------	---