

Technical Data Sheet Rev 05.230703

USB 3.0 4 Port Industrial Din Rail Mount Hub w/Power Adapter

Model Number: GM-HU34-PS



Features

- Includes Mounting brackets and DinRail Clip for mounting options
- Supports UASP function (with Windows 8 native USB 3.0 Host driver only)
- Redundant 9VDC to 24VDC power input
- Over-current detection and protection circuit design
- Compliant with Universal Serial Bus 3.0 Specification

Package Contents

-

Specifications

OVERVIEW

Model No	GM-HU34-PS
Product Type	USB Hub
Compliance	None or N/A
UPC	045079158474
Country of Origin	China
LED indicators	None or N/A
Chipset	VL811-Q8P
Electrical Protections	15kv

PHYSICAL

Ship Weight (lbs)	1.57 lbs
Ship Weight (kg)	0.71 kg
Material	
Color	Black
Mountable	

Specifications Cont.

CONNECTIONS

USB Specification	USB 3.2 Gen 1
Maximum Data Rate	5 Gbps
Downstream Port Count	4
Downstream Port Type	4x Type A USB 3.2 G1 / 3.0
Works as Standalone Charger	N - Requires Host to function
Can be Bus Powered	N - External Power Required

Power

Input Voltage	9 ~ 24V DC
Idle Power Draw	13mA @ 12V Terminal Power
Max Power Draw	24W
Max Per Port Draw	1A (5W)
Supported Charge Protocols	CDP

ENVIRONMENTAL

Operating Temperature	0C ~ 60C
Storage Temperature	-20C ~ 70C
Operating Humidity	15 ~ 85% RH

OS SUPPORT

Supported Operating Systems	OS independent - No software or drivers required
-----------------------------	--

WARRANTY

Warranty Period	1 Year
-----------------	--------

PRODUCT URL

GM-HU34-PS Product Page	
-------------------------	--