

Technical Data Sheet

USB C to Serial RS232 16 Inch Adapter with LED Indicators USB 2.0

Model Number: GM-FTDI2-LED16-C Rev 03.210315



This NEW 16 inch USB C to Serial RS232 adapter uses the new type-C USB connector technology for easy, reversible connections. The same great tool of choice when supporting serial peripherals in newer computers without serial support with a C port host. Supported by Windows 10, this is an ideal solution for serial device support.

Features

- Supports reversible USB type-C connection only, can not be connected to any other USB port.
- DA RS-232 Port support 56K Modem support Serial Mouse support+ Serial PC camera support.
- Fully compliant with USB Spec 2.0 Compliant USB Spec1.1.
- ESD Protection for RS-232 I/O' +-15KV RS-232 for DTE Mode
- Supported OS platforms are Windows 7, 8 and 10 as well as Linux and MacOS 10.X

Product Information

- Model Number: GM-FTDI2-LED16-C
- Packing List:

0



Specifications

OVERVIEW	
Product Type	Serial Adapter
Electrical Protections	15KV ESD Protection
Mountable	
Material	
Compliance	N/A
LED indicators	All Signals
Requires Host to Function	

0

Serial Modes	RS232
RS232 Signals	DCD, RxD, TxD, DTR, GND, DSR, RTS, CTS, RI
RS422 Signals	
RS485 2-wire Signals	
RS485 4-wire Signals	

SERIAL SPECS

Maximum Data Rate	460.8 Kbps
Minimum Data Rate	300 baud/bps
Data Bits	
Parity	
Stop Bits	
Flow Control	
FIFO	

lbs

0.1870 lbs



Specifications Cont. ENVIRONMENTAL

Operating Temperature	-40C ~ 85C
Operating Humidity	5% to 95% RH
Storage Temperature	-40C ~ 85C
PHYSICAL	
Length	inches
Width	inches
Height	inches

Ship Weight OS SUPPORT

Item Weight

			_	_	\neg	\neg	т	т	т
Supported Operating Systems	Cyctomo	mo		. '					
Supported Operating Systems		11115	5	, '	- 1				

WARRANTY

Warranty Period	
Wallality Fellou	

PRODUCT URL

GM-FTDI2-LED16-C Product	LED16-C Prod	Product	ct
Page			