

Technical Data Sheet Rev 06-240719

4-Port USB 3.2 Gen 2 3 Type-C 1 Type-A Industrial Surface & DIN-Rail Mount Hub w/ ESD Surge Protection

Model Number: GM-HU34CA-DW



Features

- Power your way with a wide input voltage range of 9 ~24V DC. Power either via the included DC Barrel power supply or through a 3-Pin Terminal Block.
- Upstream: USB Type-C
- Downstream: 3x USB Type-C, 1x USB Type-A
- Power Input: 3-Pin Terminal Block, DC Barrel
- Mounting Styles: Surface, Wall, and DIN-Rail

Package Contents

- 3-Pin Terminal Block
- DIN rail bracket
- Hub
- Mounting Bracket
- Power Cable
- Power Supply
- Screw Pack
- Screw Lock USB Cable

Specifications

OVERVIEW

Model No	GM-HU34CA-DW
Product Type	USB Hub
Compliance	None or N/A
UPC	045079164116
Country of Origin	China
LED indicators	Port Status Power
Electrical Protections	15KV

PHYSICAL

Ship Weight (lbs)	1.12 lbs
Ship Weight (kg)	0.51 kg
Item Weight	1.12 lbs
Length	4.45 inches
Width	2.09 inches
Height	1.02 inches
Material	Steel
Color	Black
Mountable	Din-Rail Mount Surface Mount Wall Mount

Specifications Cont.

CONNECTIONS	
USB Specification	USB 3.2 Gen 2
Upstream Port Type	Type C
Maximum Data Rate	10 Gbps
Downstream Port Count	4
Downstream Port Type	1x Type A USB 3.2 G2 2x Type C USB 3.2 G2
Works as Standalone Charger	Y - Can be used without Host
Can be Bus Powered	Y - Supports Bus Power
POWER	
Input Voltage	9 ~ 24V DC
Power Connector	DC barrel, 2.5 ID x 5.5 OD, Center Pin Positive
ENVIRONMENTAL	
Operating Temperature	0C ~ 60C
Storage Temperature	-20C ~ 70C
Operating Humidity	15 ~ 85% RH
OS SUPPORT	
Supported Operating Systems	OSX 10 Windows 11 Windows 10 Windows 8 Windows 7
WARRANTY	
Warranty Period	1 Year
PRODUCT URL	
Mfg Page	https://www.gearmo.com/shop/4-port-usb-3-2-gen-2-3-type-c-1-type-a-industrial-surface-din-rail-mount-hub-w-esd-surge-protection/