

Technical Data Sheet Rev 06-240705

4-Port USB 3.2 Gen 2 Type-C Industrial Surface & DIN-Rail Mount Hub w/ ESD Surge Protection

Model Number: GM-HU34CC-DW



Features

- Upstream: USB Type-C
- Downstream: 4x USB Type-C
- Power Input: 3-Pin Terminal Block, DC Barrel
- Mounting Styles: Surface, Wall, and DIN-Rail
- ESD: Surge protection up to 15kV

Package Contents

- DIN rail bracket
- Hub
- Mounting Bracket
- Power Supply
- Screw Lock USB Cable
- Screw Pack

Specifications

OVERVIEW

Model No	GM-HU34CC-DW
Product Type	USB Hub
Compliance	None or N/A
UPC	045079164079
Country of Origin	China
LED indicators	Port Status Power
Chipset	VL822Q7
Electrical Protections	15KV

PHYSICAL

Ship Weight (lbs)	1.12 lbs
Ship Weight (kg)	0.51 kg
Item Weight	1.12 lbs
Length	4.45 inches
Width	2.09 inches
Height	1.02 inches
Material	Steel
Color	Black
Mountable	Din-Rail Mount Surface Mount Wall Mount

Specifications Cont.

CONNECTIONS	
USB Specification	USB 3.2 Gen 2
Upstream Port Type	Type C
Maximum Data Rate	10 Gbps
Downstream Port Count	4
Downstream Port Type	Type-C
Works as Standalone Charger	Y - Can be used without Host
Can be Bus Powered	Y - Supports Bus Power
POWER	
Input Voltage	9 ~ 24V DC
Power Connector	DC barrel, 2.5 ID x 5.5 OD, Center Pin Positive
Max Power Draw	60W
Max Per Port Draw	15W @ 3A
ENVIRONMENTAL	
Operating Temperature	-10C ~ 50C
Storage Temperature	-20C ~ 60C
Operating Humidity	5% to 85% RH
OS SUPPORT	
Supported Operating Systems	OS independent - No software or drivers required
WARRANTY	
Warranty Period	1 Year
PRODUCT URL	
Mfg Page	https://www.gearmo.com/shop/4-port-usb-3-2-gen-2-type-c-industrial-surface-din-rail-mount-hub-w-esd-surge-protection/