

Technical Data Sheet Rev 06-240719

7-Port USB 3.2 Gen 2 2 Type-C 5 Type-A Industrial Surface & DIN-Rail Mount Hub w/ ESD Surge Protection

Model Number: GM-HU37CA-DW



Features

- Expand your host system's peripheral capabilities with 2 USB Type-C ports and 5 additional USB Type-A ports
- Keep your connections and peripherals safe with extensive ESD surge protection.
- Housed in a steel metal chassis, this hub is ready to tackle harsh industrial environments.
- Power your way with a wide input voltage range of 9 ~30V DC.
- Power either via the included DC Barrel power supply or through a 3-Pin Terminal Block.

Package Contents

- DIN rail bracket
- Hub
- Mounting Bracket
- Screw Pack
- USB Cable

Specifications

OVERVIEW

Model No	GM-HU37CA-DW
Product Type	USB Hub
Compliance	None or N/A
UPC	045079164116
Country of Origin	Taiwan
LED indicators	Power
Chipset	VL817Q7S VL822Q7
Electrical Protections	N/A

PHYSICAL

Ship Weight (lbs)	1.25 lbs
Ship Weight (kg)	0.57 kg
Item Weight	0.64375 lbs
Length	5.5 inches
Width	2.75 inches
Height	1 inches
Material	Steel
Color	Black
Mountable	Din-Rail Mount Surface Mount Wall Mount

Specifications Cont.

CONNECTIONS	
USB Specification	USB 3.2 Gen 2
Upstream Port Type	Type C
Maximum Data Rate	10 Gbps
Downstream Port Count	7
Downstream Port Type	5x Type A USB 3.2 G2 2x Type C USB 3.2 G2
Works as Standalone Charger	N - Requires Host to function
Can be Bus Powered	N - External Power Required
POWER	
Input Voltage	9 ~ 30V DC
Power Connector	Phoenix 3-pin
ENVIRONMENTAL	
Operating Temperature	-10C ~ 50C
Storage Temperature	1960
Operating Humidity	5% to 85% RH
OS SUPPORT	
Supported Operating Systems	OS independent - No software or drivers required
WARRANTY	
Warranty Period	1 Year
PRODUCT URL	
Mfg Page	https://www.gearmo.com/shop/7-port-usb-3-2-gen-2-3-type-c-1-type-a-industrial-surface-din-rail-mount-hub-w-esd-surge-protection-copy/