

Technical Data Sheet Rev 06-241203

# USB to RS-422/485 Converter FTDI CHIP w/ Terminals

Model Number: USA-482422



## Features

- This USB to RS-485/ RS-422 serial converter with LED for RX, TX, and Power.
- Asynchronous, Point-to-Point, Point-to-Multipoint, 2-Wire (Half-Duplex), 4-Wire (Full-Duplex)
- Transmission Rates: 300 to 921.6kbps, automatic detection of signaling rate
- 15KV ESD Surge protection
- OS Support: Windows 7, 8, 9, 10, & Windows 11, Linux, Mac OS 10.X

## Package Contents

- Driver/Software Disk
- USB Serial Adapter

## Specifications

### OVERVIEW

Model No	USA-482422
Alias	GM-482422
Product Type	USB Serial Adapter
Compliance	RoHS
UPC	729440692391
Country of Origin	China
LED indicators	Power   RX / TX
Chipset	FTDI FT232RL
Electrical Protections	15KV

### PHYSICAL

Ship Weight (lbs)	0.07 lbs
Ship Weight (kg)	0.03 kg
Material	Plastic
Color	Black

**Specifications Cont.****CONNECTIONS**

USB Specification	USB 2.0
Connector(s)	DB9 Male w/ Nuts   USB 2.0 Type A Male Fixed Cable

**SERIAL SPECS**

Maximum Data Rate	921.6 Kbps
Minimum Data Rate	300 baud/bps
Serial Modes	RS422   RS485
RS422 Signals	TxD-, TxD+, RxD+, RxD-, GND
RS485 2-wire Signals	T/R+, T/R-, GND

**ENVIRONMENTAL**

Operating Temperature	-40C ~ 85C
Storage Temperature	-40C ~ 85C
Operating Humidity	5% to 95% RH

**OS SUPPORT**

Supported Operating Systems	Linux   OSX 10   Windows 11   Windows 10   Windows 8
-----------------------------	--

**WARRANTY**

Warranty Period	1 Year
-----------------	--------

**PRODUCT URL**

Product Page	<a href="https://www.gearmo.com/shop/usb-to-rs485-rs422-converter-ftdi-chip-with-terminals/">https://www.gearmo.com/shop/usb-to-rs485-rs422-converter-ftdi-chip-with-terminals/</a>
--------------	---