

Technical Data Sheet Rev 06-250508

USB Industrial 2-Port Serial Adapter RS-232 w/FTDI Chipset, RX/TX LED Indicators, DIN Rail & Surface Mounting Brackets

Model Number: GM-FTDI2X-M



Features

- Utilizes FT232RL FTDI Chip set
- Automatically configures the additional COM ports and retains assigned serial COM port values upon disconnection
- Plug and Play allows easy installation with no resource conflicts - Supports up to Windows 11, Linux, and macOS
- Perfect for connecting serial modems, bar code scanners, CNC routers, and other legacy serial devices
- Ready to mount on a surface/wall or DIN rail with included clips. Includes 6ft USB cable.

Package Contents

- DIN rail bracket
- Mounting Bracket
- Screw Pack
- USB Cable
- USB Serial Adapter

Specifications

OVERVIEW

Model No	GM-FTDI2X-M	Product Type	USB Serial Adapter
Compliance	REACH RoHS	UPC	045079161504
Country of Origin	China	LED indicators	Power TX/RX
Chipset	FTDI FT232RL	Electrical Protections	15kV

PHYSICAL

Ship Weight (lbs)	0.95 lbs	Ship Weight (kg)	0.43 kg
Item Weight	0.3625 lbs	Length	3.06 inches
Width	2.26 inches	Height	0.99 inches
Material	Steel	Color	Black
Mountable	Din-Rail Mount Surface Mount Wall Mount		

Specifications Cont.

CONNECTIONS

USB Specification	USB 2.0
Connector(s)	DB9 Male w/ Nuts USB 2.0 Type B Female

SERIAL SPECS

Maximum Data Rate	921.6 Kbps
Minimum Data Rate	300 baud/bps
Parity	Odd, Even, Mark, Space, None
Stop Bits	1, 2
Serial Modes	RS232

ENVIRONMENTAL

Operating Temperature	0C ~ 40C
Storage Temperature	-20c ~ 50C
Operating Humidity	5% to 95% RH

OS SUPPORT

Supported Operating Systems	Linux OSX 10 Windows 11 Windows 10 Windows 8 Windows 7
------------------------------------	--

WARRANTY

Warranty Period	1 Year
------------------------	--------

PRODUCT URL

Product Page	https://www.gearmo.com/shop/gearmo-usb-2-port-serial-rs232-featuring-ftdi-chipset-with-led-indicators/
---------------------	---