

**Technical Data Sheet Rev 06-250812** 

# 1 Port USB to Serial RS-232 Hub w/ FTDI Chipset & LED Indicators - Rugged Metal Housing Ideal for Mounting

Model Number: GM-FTDI1X-M











### **Features**

- Adds 1 standard RS-232 serial port to your laptop, desktop, or other host system utilizing a high performance FTDI Chipset
- 25kV of protection from static electricity and surges to keep your connected equipment safe from damage.
- COM retention saves the assigned COM port number even after accidental disconnects.
- Surface mount or DIN-Rail mount this adapter with the included mounting brackets.
- Supported OS: Windows 11, 10, 8, 7, Linux, and MacOS.

# **Package Contents**

- DIN rail bracket
- Hub
- Mounting Bracket
- Screw Pack
- USB Cable

## Specifications

OVERVIEW			
Model No	GM-FTDi1X-M	Product Type	Serial Adapter
Compliance	None or N/A	UPC	045079161498
Country of Origin	China	LED indicators	Power   TX/RX
Chipset	FTDI FT2232H	Electrical Protections	25kv

# **PHYSICAL**

Ship Weight (lbs)	0.32 lbs	Ship Weight (kg)	0.15 kg
Item Weight	0.324 lbs	Length	2.56 inches
Width	1.97 inches	Height	0.98 inches
Material	Steel	Color	Black
Mountable	Din-Rail Mount   Surface Mount   Wall Mount		



Specifications Cont.		
CONNECTIONS		
USB Specification	USB 2.0	
Connector(s)	DB9 Male w/ Nuts   USB 2.0 Type B Female	
Maximum Data Rate	921.6kbps	
SERIAL SPECS		
Maximum Data Rate	921.6 Kbps	
Serial Modes	RS232	
RS232 Signals	TxD, RxD, RTS, CTS, DSR, DTR, DCD, RI, GND	
ENVIRONMENTAL		
Operating Temperature	0C ~ 50C	
Storage Temperature	-20C ~ 70C	
Operating Humidity	15 ~ 85% RH	
OS SUPPORT		
Supported Operating Systems	Linux   OSX 10   Windows 11   Windows 10   Windows 8   Windows 7	
WARRANTY		
Warranty Period	1 Year	
PRODUCT URL		
Product Page	https://www.gearmo.com/shop/1-port-usb-to-serial-rs-232-hub-w-ftdi-chipset-led-indicators-rugged-metal-housing-ideal-for-mounting/	