

**Technical Data Sheet Rev 06-250731** 

# 4 Port RS232 to USB FTDI Chip Adapter w/ RX and TX Status LEDs

Model Number: GM-FTDI4X-LED









### **Features**

- Plug & Play to instantly add 4 standard serial ports to your desktop, laptop, or other device
- Compatible with many peripherals such as GPS, modems, printers, scanners, digital cameras, and more
- Baud rates up to 921.6kbps
- Dual 16 Byte hardware data buffer (up/down stream)
- Cable Length: 3 feet

# **Package Contents**

- Driver/Software Disk
- USB Serial Adapter

## Specifications

OVERVIEW			
Model No	GM-FTDI4X-LED	Product Type	USB Serial Adapter
Compliance	None or N/A	UPC	045079162945
Country of Origin	China	LED indicators	Power   TX/RX
Chipset	2138	Electrical Protections	15KV
PHYSICAL		·	

#### Ship Weight (lbs) 0.51 lbs Ship Weight (kg) 0.23 kg **Item Weight** 0.4 lbs Length 60 inches Width 1.57 inches Height 0.78 inches Color Material **Plastic** Black Cable Length (in) 60 Cable Length (m) 1.52



Specifications Cont.			
CONNECTIONS			
Connector(s)	DB9 Male w/ Screws   USB 2.0 Type A Male Fixed Cable		
Maximum Data Rate	921.6Kbps		
SERIAL SPECS			
Maximum Data Rate	921.6 Kbps		
Minimum Data Rate	300 baud/bps		
Serial Modes	RS232		
RS232 Signals	DCD, RxD, TxD, DTR, GND, DSR, RTS, CTS, RI		
ENVIRONMENTAL			
Operating Temperature	-40 C ~ 85 C		
Storage Temperature	-40C ~ 85C		
Operating Humidity	5% to 95% RH		
OS SUPPORT			
Supported Operating Systems	Linux   OSX 10   Windows 11   Windows 10   Windows 8		
WARRANTY			
Warranty Period	1 Year		
PRODUCT URL			
Product Page	https://www.gearmo.com/shop/4-port-usb-to-serial-adapter-with-rx-tx-indicators/		