

Technical Data Sheet Rev 06-250826

Industrial USB 4 Port Serial RS-232 Adapter w/FTDI Chipset, COM Retention, RX/TX LED Indicators, DIN Rail Mount Bracket, & Surface Mounting Brackets

Model Number: GM-FTDI4X-M











Features

- Adds 4 standard RS-232 serial ports to your laptop, desktop, or other host system utilizing a high performance FTDI Chipset
- Connect serial modems, bar code scanners, CNC routers, and other legacy serial devices
- Supports Self Power and Variable Voltage input 9~48V
- COM retention saves the assigned COM port number even after accidental disconnects
- Includes hardware for surface/wall or DIN rail mounting

Package Contents

- 3-Pin Terminal Block
- DIN rail bracket
- Driver/Software Disk
- Mounting Bracket
- Screw Pack
- USB Cable
- USB Serial Adapter
- User Manual

Specifications

OVERVIEW

Model No	GM-FTDI4X-M	Product Type	USB Serial Adapter
Compliance	REACH RoHS	UPC	045079161573
Country of Origin	China	LED indicators	Power TX/RX
Chipset	FTDI FT4232HL	Electrical Protections	N/A

PHYSICAL

Ship Weight (lbs)	1.02 lbs	Ship Weight (kg)	0.46 kg
Length	6.299 inches	Width	2.461 inches
Height	0.906 inches	Material	Steel
Color	Black	Mountable	Din-Rail Surface Mount Wall Mount



Specifications Cont.			
CONNECTIONS			
USB Specification	USB 2.0		
SERIAL SPECS			
Maximum Data Rate	921.6 Kbps		
Minimum Data Rate	300 baud/bps		
Data Bits	7, 8		
Parity	Odd, Even, Mark, Space, None		
Stop Bits	1, 2		
FIFO	4096 byte Transmit and Receive		
Serial Modes	RS232		
RS232 Signals	DCD, RxD, TxD, DTR, GND, DSR, RTS, CTS, RI		
ENVIRONMENTAL			
Operating Temperature	0C ~ 40C		
Storage Temperature	-20c ~ 50C		
Operating Humidity	5% to 95% RH		
OS SUPPORT			
Supported Operating Systems	Linux OSX 10 Windows 11 Windows 10 Windows 8		
WARRANTY			
Warranty Period	1 Year		
PRODUCT URL			
Product Page	https://www.gearmo.com/shop/gearmo-usb-4-port-serial-rs232-featuring-ftdi-chipset-with-rx-tx-led-indicators-industrial-version/		