

Technical Data Sheet Rev 06-250918

Pro 5ft. USB to RS-485/422 Serial Adapter FTDI Chip - Windows 11 Supported

Model Number: **US-485422**



Features

- Static consumption less than 80mA, dynamic average consumption less than 150mA
- Asynchronous, point to point, point to multi-point, half duplex
- No IRQs, DMA or required. No IRQ Conflicts
- Standard USB 1.1/2.0, EIA RS-485, RS-422 standard works with Windows 11
- Serial connector type RS-485 / RS422 side DB-9 male or optional terminal block

Package Contents

- Driver/Software Disk
- USB Serial Adapter

Specifications

OVERVIEW

Model No	US-485422	Alias	GM-485422
Product Type	USB Serial Adapter	Compliance	RoHS
UPC	729440692384	Country of Origin	China
LED indicators	Power RX / TX	Electrical Protections	15kV

PHYSICAL

Ship Weight (lbs)	0.21 lbs	Ship Weight (kg)	0.1 kg
Length	2.76 inches	Width	1.38 inches
Height	0.75 inches	Material	Plastic
Color	Blue	Mountable	N/A
Cable Length (ft)	5	Cable Length (in)	60
Cable Length (m)	1.52		

Specifications Cont.

CONNECTIONS

USB Specification	USB 2.0
Connector(s)	6-Pin Terminal Block DB9 Male w/ Nuts USB 2.0 Type A Male Fixed Cable

SERIAL SPECS

Maximum Data Rate	921.6 Kbps
Minimum Data Rate	300 baud/bps
Serial Modes	RS422 RS485
RS422 Signals	T+, T-, R+, R-, GND
RS485 2-wire Signals	DATA+, DATA-, GND

ENVIRONMENTAL

Operating Temperature	-25C ~ 70C
Storage Temperature	-25C ~ 70C
Operating Humidity	5% to 95% RH

OS SUPPORT

Supported Operating Systems	Linux OSX 10 Windows 11 Windows 10 Windows 8
------------------------------------	--

WARRANTY

Warranty Period	1 Year
------------------------	--------

PRODUCT URL

Product Page	https://www.gearmo.com/shop/usb-to-rs485-rs422-converter-with-ftdi-chip/
---------------------	---