

Technical Data Sheet Rev 06-250918

# 36in FTDI USB to Serial Cable for Mac PC Linux with Windows 11

Model Number: USA-FTDI-36



## Features

- Hi-Speed 36 Inch Black USB Serial Adapter - Supports Cisco Break Sequence
- USB Bus Powered - No External Power Required
- Built-in static and surge protection up to 600W
- Requires no IRQ, DMA, or I/O port resources
- OS Compatibility: Windows XP, 2003, CE, Vista, Windows 7, 8, 10, and 11 as well as Linux and Mac OS 10.X

## Package Contents

- USB Serial Adapter
- User Manual

## Specifications

### OVERVIEW

Model No	USA-FTDI-36	Product Type	USB Serial Adapter
Compliance	None or N/A	UPC	729440625993
Country of Origin	China	LED indicators	None or N/A
Chipset	FTDI FT232RQ	Electrical Protections	15KV

### PHYSICAL

Ship Weight (lbs)	0.11 lbs	Ship Weight (kg)	0.05 kg
Material	Plastic	Color	Black
Mountable	N/A	Cable Length (ft)	3
Cable Length (in)	36	Cable Length (m)	0.91

## Specifications Cont.

### CONNECTIONS

<b>USB Specification</b>	USB 2.0
<b>Connector(s)</b>	DB9 Male w/ Screws   USB 2.0 Type A Male
<b>Maximum Data Rate</b>	115.2Kbps

### SERIAL SPECS

<b>Maximum Data Rate</b>	115.2 kbps
<b>Minimum Data Rate</b>	300 baud/bps
<b>FIFO</b>	128 byte transmit 384 byte receive
<b>Serial Modes</b>	RS232
<b>RS232 Signals</b>	RxD, TxD, GND, RTS, CTS

### ENVIRONMENTAL

<b>Operating Temperature</b>	-25C ~ 70C
<b>Storage Temperature</b>	-25C ~ 70C
<b>Operating Humidity</b>	5% to 95% RH

### OS SUPPORT

<b>Supported Operating Systems</b>	Linux   OSX 10   Windows 11   Windows 10   Windows 8
------------------------------------	------------------------------------------------------

### WARRANTY

<b>Warranty Period</b>	1 Year
------------------------	--------

### PRODUCT URL

<b>Product Page</b>	<a href="https://www.gearmo.com/shop/usb-to-rs232-serial-adapter-3ft-cable-gm-ftdi-36/">https://www.gearmo.com/shop/usb-to-rs232-serial-adapter-3ft-cable-gm-ftdi-36/</a>
---------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------