

Technical Data Sheet Rev 06-251001

4-Port USB 3.2 Gen 2 3 Type-C 1 Type-A Industrial Surface & DIN-Rail Mount Hub w/ ESD Surge Protection

Model Number: GM-HU34CA-DW



Features

- Power your way with a wide input voltage range of 9 ~24V DC. Power either via the included DC Barrel power supply or through a 3-Pin Terminal Block.
- Upstream: USB Type-C
- Downstream: 3x USB Type-C, 1x USB Type-A
- Power Input: 3-Pin Terminal Block, DC Barrel
- Mounting Styles: Surface, Wall, and DIN-Rail

Package Contents

- 3-Pin Terminal Block
- DIN rail bracket
- Hub
- Mounting Bracket
- Power Cable
- Power Supply
- Screw Pack
- Screw Lock USB Cable

Specifications

OVERVIEW

Model No	GM-HU34CA-DW	Product Type	USB Hub
Compliance	RoHS	UPC	045079164062
Country of Origin	China	LED indicators	Port Status Power
Electrical Protections	15KV		

PHYSICAL

Ship Weight (lbs)	1.12 lbs	Ship Weight (kg)	0.51 kg
Item Weight	1.12 lbs	Length	4.45 inches
Width	2.09 inches	Height	1.02 inches
Material	Steel	Color	Black
Mountable	Din-Rail Mount Surface Mount Wall Mount		

Specifications Cont.

CONNECTIONS

USB Specification	USB 3.2 Gen 2
Upstream Port Type	Type C
Maximum Data Rate	10 Gbps
Downstream Port Count	4
Downstream Port Type	1x Type A USB 3.2 G2 2x Type C USB 3.2 G2
Works as Standalone Charger	Y - Can be used without Host
Can be Bus Powered	Y - Supports Bus Power

POWER

Input Voltage	9 ~ 24V DC
Power Connector	DC barrel, 2.5 ID x 5.5 OD, Center Pin Positive

OS SUPPORT

Supported Operating Systems	OSX 10 Windows 11 Windows 10 Windows 8 Windows 7
-----------------------------	--

WARRANTY

Warranty Period	1 Year
-----------------	--------

PRODUCT URL

Product Page	https://www.gearmo.com/shop/4-port-usb-3-2-gen-2-3-type-c-1-type-a-industrial-surface-din-rail-mount-hub-w-esd-surge-protection/
--------------	---