

Technical Data Sheet Rev 06-251114

6-Port USB 3.2 Gen 1 Industrial Metal Hub w/15KV ESD Protection

Model Number: GM-6AHU3-PE



Features

- Add 6 front-facing USB Type-A ports for easy access, with clearly labeled numbered ports and power connections
- Fast data transfer speeds up to 5Gbps and backward compatibility
- Rugged metal housing with 15kV ESD and 600W surge protection per port
- Includes both DIN rail and surface mount hardware for flexible installation
- Includes 12V/5A power supply

Package Contents

- 3-Pin Terminal Block
- DIN rail bracket
- Hub
- Mounting Bracket
- Power Cable
- Power Supply
- Screw Pack
- USB Cable

Specifications

OVERVIEW

Model No	GM-6AHU3-PE	Product Type	USB Hub
Compliance	REACH RoHS	UPC	045079165199
Country of Origin	China	LED indicators	None or N/A
Chipset	VL817S	Electrical Protections	15kV

PHYSICAL

Ship Weight (lbs)	1.74 lbs	Ship Weight (kg)	0.79 kg
Item Weight	0.46 lbs	Length	3 inches
Width	2.6 inches	Height	0.98 inches
Material	Steel	Color	Black
Mountable	Surface / Wall Mount Din-Rail		

Specifications Cont.

CONNECTIONS

USB Specification	USB 3.2 Gen 1
Upstream Port Type	USB 3.2G1 / 3.0 Type-B Female
Maximum Data Rate	5Gbps
Downstream Port Count	6
Downstream Port Type	6 x Type A USB 3.2 G1 / 3.0
Can be Bus Powered	N - External Power Required

POWER

Input Voltage	9~24V DC
Power Connector	Phoenix 3-pin
Max Power Draw	2.4A per port (Max), total 60W max

ENVIRONMENTAL

Operating Temperature	0C ~ 50C
Storage Temperature	-20C ~ 70C
Operating Humidity	15 ~ 85% RH

OS SUPPORT

Supported Operating Systems	Linux OSX 10 Windows 11 Windows 10 Windows 8 Windows 7 Windows Vista Windows XP
------------------------------------	---

PRODUCT URL

Product Page	https://www.gearmo.com/shop/6-port-usb-3-2-gen-1-industrial-metal-hub-w-15kv-esd-protection/
---------------------	---