

Technical Data Sheet Rev 06-260122

2-Port Professional USB 2.0 to Serial Converter w/ RX/TX Status LED

Model Number: **GM-FTDI2X-LED**



Features

- RXD, TXD Status LED Array
- Easy Plug and Play installation
- Baud rates up to 921.6kbps
- Dual 16 Byte hardware data buffer (up/down stream)
- Cable Length: 3 ft

Package Contents

- Driver/Software Disk
- USB Serial Adapter
- User Manual

Specifications

OVERVIEW

Model No	GM-FTDI2X-LED	Product Type	USB Serial Adapter
Compliance	CE REACH RoHS	UPC	045079162938
Country of Origin	China	LED indicators	Power TX/RX
Chipset	FTDI FT2232D	Electrical Protections	15KV

PHYSICAL

Ship Weight (lbs)	0.39 lbs	Ship Weight (kg)	0.18 kg
Material	Plastic	Color	Black
Cable Length (ft)	3	Cable Length (in)	60
Cable Length (m)	1.52		

Specifications Cont.

CONNECTIONS

USB Specification	USB 2.0
Connector(s)	DB9 Male w/ Nuts USB 2.0 Type A Male Fixed Cable
Maximum Data Rate	921.6Kbps

SERIAL SPECS

Maximum Data Rate	921.6 Kbps
Minimum Data Rate	300 baud/bps
Serial Modes	RS232
RS232 Signals	DCD, RxD, TxD, DTR, GND, DSR, RTS, CTS, RI

ENVIRONMENTAL

Operating Temperature	-40 C ~ 85 C
Storage Temperature	-40C ~ 85C
Operating Humidity	5% to 95% RH

OS SUPPORT

Supported Operating Systems	Linux OSX 10 Windows 11 Windows 10 Windows 8 Windows 7
------------------------------------	--

WARRANTY

Warranty Period	1 Year
------------------------	--------

PRODUCT URL

Product Page	https://www.gearmo.com/shop/2-port-usb-to-serial-adapter-with-rx-tx-led-indicators/
---------------------	---