

Technical Data Sheet Rev 06-260122

2 Port USB Type-C To Serial Adapter w/ Per Port Rx / TX Status LED Matrix

Model Number: GM-FTDI2XC-LED



Features

- Easy Plug and Play Installation
- RXD, TXD Status LED Array
- USB Interface: Standard Type-C female
- Automatic handshake support & Baud rates up to 921.600bps
- Dual 16 Byte hardware data buffer (up/down stream)

Package Contents

- USB Serial Adapter
- User Manual

Specifications

OVERVIEW

Model No	GM-FTDI2XC-LED	Product Type	USB Serial Adapter
Compliance	CE REACH RoHS	UPC	045079163027
Country of Origin	China	LED indicators	Power TX/RX
Electrical Protections	15KV		

PHYSICAL

Ship Weight (lbs)	0.39 lbs	Ship Weight (kg)	0.18 kg
Item Weight	0.281 lbs	Length	36 inches
Material	Plastic	Color	Black
Cable Length (in)	60	Cable Length (m)	1.52

Specifications Cont.

CONNECTIONS

Maximum Data Rate	921.6Kbps
-------------------	-----------

SERIAL SPECS

Maximum Data Rate	921.6 Kbps
Minimum Data Rate	300 baud/bps
Serial Modes	RS232
RS232 Signals	DCD, RxD, TxD, DTR, GND, DSR, RTS, CTS, RI

ENVIRONMENTAL

Operating Temperature	-40C ~ 85C
Storage Temperature	-40C ~ 85C
Operating Humidity	5% to 95% RH

OS SUPPORT

Supported Operating Systems	Linux OSX 10 Windows 11 Windows 10 Windows 8 Windows 7
-----------------------------	--

WARRANTY

Warranty Period	1 Year
-----------------	--------

PRODUCT URL

Product Page	https://www.gearmo.com/shop/2-port-usb-to-serial-adapter-with-rx-tx-led-indicators/
--------------	---