

Technical Data Sheet Rev 06-260122

4 Port RS232 to USB FTDI Chip Adapter w/ RX and TX Status LEDs

Model Number: **GM-FTDI4X-LED**



Features

- Plug & Play to instantly add 4 standard serial ports to your desktop, laptop, or other device
- Compatible with many peripherals such as GPS, modems, printers, scanners, digital cameras, and more
- Baud rates up to 921.6kbps
- Dual 16 Byte hardware data buffer (up/down stream)
- Cable Length: 3 feet

Package Contents

- Driver/Software Disk
- USB Serial Adapter

Specifications

OVERVIEW

Model No	GM-FTDI4X-LED	Product Type	USB Serial Adapter
Compliance	CE REACH RoHS	UPC	045079162945
Country of Origin	China	LED indicators	Power TX/RX
Chipset	FTDI FT4232H	Electrical Protections	15KV

PHYSICAL

Ship Weight (lbs)	0.51 lbs	Ship Weight (kg)	0.23 kg
Item Weight	0.4 lbs	Length	60 inches
Width	1.57 inches	Height	0.78 inches
Material	Plastic	Color	Black
Cable Length (ft)	3	Cable Length (in)	60
Cable Length (m)	1.52		

Specifications Cont.**CONNECTIONS**

Connector(s)	DB9 Male w/ Screws USB 2.0 Type A Male Fixed Cable
Maximum Data Rate	921.6Kbps

SERIAL SPECS

Maximum Data Rate	921.6 Kbps
Minimum Data Rate	300 baud/bps
Serial Modes	RS232
RS232 Signals	DCD, RxD, TxD, DTR, GND, DSR, RTS, CTS, RI

ENVIRONMENTAL

Operating Temperature	-40 C ~ 85 C
Storage Temperature	-40C ~ 85C
Operating Humidity	5% to 95% RH

OS SUPPORT

Supported Operating Systems	Linux OSX 10 Windows 11 Windows 10 Windows 8
------------------------------------	--

WARRANTY

Warranty Period	1 Year
------------------------	--------

PRODUCT URL

Product Page	https://www.gearmo.com/shop/4-port-usb-to-serial-adapter-with-rx-tx-indicators/
---------------------	---