

Technical Data Sheet Rev 06-260122

4 Port USB Type-C To Serial Adapter with Per Port TX/RX LEDs

Model Number: GM-FTDI4XC-LED



Features

- Easy Plug and Play installation
- RXD, TXD Status LED Array
- USB Interface: Standard Type-C female
- Baud rates up to 921.600bps & Automatic handshake support
- Quad 16 Byte hardware data buffer (up/down stream)

Package Contents

- Driver/Software Disk
- USB Serial Adapter
- User Manual

Specifications

OVERVIEW

Model No	GM-FTDI4XC-LED	Product Type	USB Serial Adapter
Compliance	CE REACH RoHS	UPC	045079163034
Country of Origin	China	LED indicators	Power TX/RX
Chipset	FTDI FT4232H	Electrical Protections	N/A

PHYSICAL

Ship Weight (lbs)	0.48 lbs	Ship Weight (kg)	0.22 kg
Item Weight	0.375 lbs	Length	60 inches
Width	1.57 inches	Height	0.78 inches
Material	Plastic	Color	Black
Cable Length (in)	60	Cable Length (m)	1.52

Specifications Cont.

CONNECTIONS

USB Specification	USB 2.0
Connector(s)	USB Type C Male
Maximum Data Rate	921.6Kbps

SERIAL SPECS

Maximum Data Rate	921.6 Kbps
Minimum Data Rate	300 baud/bps
Serial Modes	RS232
RS232 Signals	DCD, RxD, TxD, DTR, GND, DSR, RTS, CTS, RI

ENVIRONMENTAL

Operating Temperature	-40C ~ 85C
Storage Temperature	-40C ~ 85C
Operating Humidity	5% to 95% RH

OS SUPPORT

Supported Operating Systems	Linux OSX 10 Windows 11 Windows 10 Windows 8
-----------------------------	--

WARRANTY

Warranty Period	1 Year
-----------------	--------

PRODUCT URL

Product Page	https://www.gearmo.com/shop/4-port-usb-type-c-to-serial-adapter-with-per-port-led-rx-tx-status-indicators/
--------------	---