

Technical Data Sheet Rev 06-260312

4-Port USB 3.2 Gen 1 Slim Industrial Metal Hub w/15KV ESD Protection

Model Number: **GM-BA4XUH-M**



Features

- Adds 4 USB 3.0 5Gbps compliant ports
- Clearly labeled port numbers and power connections
- Rugged Industrial-grade chassis for harsh environments
- Over-current detection and protection circuit design
- Wall and DIN Rail mount support

Package Contents

- 3-Pin Terminal Block
- DIN rail bracket
- Hub
- Mounting Bracket
- Screw Pack
- USB Cable

Specifications

OVERVIEW

Model No	GM-BA4XUH-M	Product Type	USB Hub
Compliance	CE FCC POP REACH RoHS	UPC	045079165274
Country of Origin	China	LED indicators	Power
Chipset	VLI 817	Electrical Protections	15kV

PHYSICAL

Ship Weight (lbs)	1.34 lbs	Ship Weight (kg)	0.61 kg
Item Weight	0.36 lbs	Length	2.88 inches
Width	2.0 inches	Height	1.0 inches
Material	Steel	Color	Black
Mountable	Surface / Wall Mount Din-Rail Mount		

Specifications Cont.

CONNECTIONS

USB Specification	USB 3.2 Gen 1
Upstream Port Type	USB 3.2G1 / 3.0 Type-B Female
Maximum Data Rate	5Gbps
Downstream Port Count	4
Downstream Port Type	4x Type A USB 3.2 G1 / 3.0
Works as Standalone Charger	Y - Can be used without Host
Can be Bus Powered	Y - Supports Bus Power

POWER

Input Voltage	9 ~ 24V DC
Power Connector	Phoenix 3-pin
Max Per Port Draw	2.4A per port max, total 40W max

ENVIRONMENTAL

Operating Temperature	0 – 50°C (32 – 122°F)
Storage Temperature	-20C ~ 70C
Operating Humidity	15 ~ 85% RH

OS SUPPORT

Supported Operating Systems	Linux OSX 10 Windows 11 Windows 10 Windows 8 Windows 7
------------------------------------	--

WARRANTY

Warranty Period	1 Year
------------------------	--------

PRODUCT URL

Product Page	https://www.gearmo.com/shop/4-port-usb-3-2-gen-1-industrial-metal-hub-w-15kv-esd-protection/
---------------------	---