

Technical Data Sheet Rev 06-260313

USB 3.0 4 Port Industrial Metal Hub w/15KV ESD Protection

Model Number: GM-HU34DW



Features

- Compliant with Universal Serial Bus 3.0 Specifications
- Power input 15kv ESD surge protection to 600W for each port
- Wall and DIN Rail mount support
- Rugged Industrial-grade Chassis for Harsh Environments
- 15kv ESD, 600w Surge supression

Package Contents

- DIN rail bracket
- Hub
- Mounting Bracket
- Power Supply
- USB Cable

Specifications

OVERVIEW

Model No	GM-HU34DW	Product Type	USB Hub
Compliance	CE FCC REACH RoHS	UPC	045079159822
Country of Origin	China	LED indicators	Port Status Power
Chipset	VL817-Q7S	Electrical Protections	15KV

PHYSICAL

Ship Weight (lbs)	1.26 lbs	Ship Weight (kg)	0.57 kg
Length	4.57 inches	Width	2.09 inches
Height	1.02 inches	Material	Steel
Color	Black	Mountable	Din-Rail Surface Mount

Specifications Cont.

CONNECTIONS

USB Specification	USB 3.2 Gen 1
Upstream Port Type	USB 3.2G1 / 3.0 Type-B Female
Maximum Data Rate	5 Gbps
Downstream Port Count	4
Downstream Port Type	4x Type A USB 3.2 G1 / 3.0
Works as Standalone Charger	N - Requires Host to function
Can be Bus Powered	N - External Power Required

POWER

Input Voltage	9 ~ 24V DC
Idle Power Draw	13 mA @12v DC
Max Power Draw	20W
Max Per Port Draw	1.5A (BC 1.2)
Supported Charge Protocols	Apple Charge 2.4A CDP DCP SDP

ENVIRONMENTAL

Operating Temperature	0C ~ 55C
Storage Temperature	-20C ~ 75C
Operating Humidity	5% to 95% RH

OS SUPPORT

Supported Operating Systems	Linux OSX 10 Windows 11 Windows 10 Windows 8 Windows 7 Windows Vista Windows XP
------------------------------------	---

WARRANTY

Warranty Period	1 Year
------------------------	--------

PRODUCT URL

Product Page	https://www.gearmo.com/shop/usb-3-4-port-industrial-metal-hub-15kv-esd-protection/
---------------------	---