

Technical Data Sheet Rev 06-260317

Industrial 4-Port USB 3.2 Gen 2 Type-C Hub w/ 15kV ESD Protection

Model Number: GM-HU34G2



Features

- Fully Compliant with USB 3.2 Gen 2 Specifications and Supports 10Gbps Data Speed
- Mounting Options for DIN Rail or Surface Mount
- 2 Downstream USB-A Ports, 2 Downstream USB-C Ports, & Upstream USB Type-C Single or Dual Screw-Locking Port
- Offers DC Barrel or 2-Pin Terminal Block Power Connector with 9~24V DC Input Voltage Range
- 15kV ESD Surge Protection for All Ports

Package Contents

- 2-Pin Terminal Block
- DIN rail bracket
- Hub
- Mounting Bracket
- Screw Pack
- USB Cable

Specifications

OVERVIEW

Model No	GM-HU34G2	Product Type	USB Hub
Compliance	CE FCC REACH RoHS	UPC	045079163188
Country of Origin	China	LED indicators	Port Status Power
Chipset	VL822-Q8	Electrical Protections	N/A

PHYSICAL

Ship Weight (lbs)	0.6 lbs	Ship Weight (kg)	0.27 kg
Item Weight	0.6 lbs	Length	5.28 inches
Width	2.21 inches	Height	1.07 inches
Material	Steel	Color	Black
Mountable	Desktop Din-Rail Mount Surface Mount Wall Mount		

Specifications Cont.

CONNECTIONS

USB Specification	USB 3.2 Gen 2
Upstream Port Type	Type C
Maximum Data Rate	10 Gbps
Downstream Port Count	4
Downstream Port Type	2x Type A USB 3.2 G2 2x Type C USB 3.2 G2
Works as Standalone Charger	Y - Can be used without Host
Can be Bus Powered	Y - Supports Bus Power

POWER

Input Voltage	9 ~ 24V DC
Min Input Voltage	9v
Max Input Voltage	24v
Power Connector	DC barrel, 2.5 ID x 5.5 OD, Center Pin Positive

ENVIRONMENTAL

Operating Temperature	0C ~ 55C
Storage Temperature	-20C ~ 75C
Operating Humidity	5% to 95% RH

OS SUPPORT

Supported Operating Systems	Linux OSX 10 Windows 11 Windows 10 Windows 8 Windows 7
------------------------------------	--

WARRANTY

Warranty Period	1 Year
------------------------	--------

PRODUCT URL

Product Page	https://www.gearmo.com/shop/industrial-4-port-usb-3-2-gen-2-type-c-hub-w-esd-protection/
---------------------	---