

Technical Data Sheet Rev 06-260330

7-Port USB 3.2 Gen 2 Type-C Industrial Surface & DIN-Rail Mount Hub w/ ESD Surge Protection

Model Number: GM-HU37C-DW



Features

- Expand your host system's peripheral capabilities with 7 USB Type-C ports.
- Keep your connections and peripherals safe with extensive ESD surge protection.
- Wide input voltage range of 9 ~24V DC. Power options via included DC Barrel power supply or 3-Pin Terminal Block.
- Screw-locking USB ports ensure secure connections.
- Versatile mounting options include Surface, Wall, and DIN-Rail.

Package Contents

- 3-Pin Terminal Block
- DIN rail bracket
- Hub
- Mounting Bracket
- Power Supply
- Screw Pack
- Screw Lock USB Cable
- User Manual

Specifications

OVERVIEW

Model No	GM-HU37C-DW	Product Type	USB Hub
Compliance	CE FCC REACH RoHS	UPC	045079164741
Country of Origin	China	LED indicators	Port Status Power
Chipset	VL822-Q7	Electrical Protections	15kV

PHYSICAL

Ship Weight (lbs)	1.74 lbs	Ship Weight (kg)	0.79 kg
Item Weight	0.59 lbs	Length	5.5 inches
Width	2.75 inches	Height	1 inches
Material	Steel	Color	Black
Mountable	Din-Rail Mount Surface Mount Wall Mount		

Specifications Cont.**CONNECTIONS**

USB Specification	USB 3.2 Gen 2
Upstream Port Type	USB 3.2G2 / 3.0 Type-C Female
Maximum Data Rate	10Gbps
Downstream Port Count	7
Downstream Port Type	7x Type C USB 3.2 G2

POWER

Input Voltage	9~24V DC
Max Power Draw	57W
Max Per Port Draw	2.4A
Supported Charge Protocols	BC 1.2

ENVIRONMENTAL

Operating Temperature	0C ~ 50C
Storage Temperature	-20C ~ 70C
Operating Humidity	15 ~ 85% RH

OS SUPPORT

Supported Operating Systems	Linux OSX 10 Windows 11 Windows 10 Windows 8 Windows 7
------------------------------------	--

WARRANTY

Warranty Period	1 Year
------------------------	--------

PRODUCT URL

Product Page	https://www.gearmo.com/shop/7-port-usb-3-2-gen-2-type-c-industrial-surface-din-rail-mount-hub-w-esd-surge-protection/
---------------------	---