

Technical Data Sheet Rev 06-260313

USB 3.0 7 Port Industrial Metal Hub w/15KV ESD Protection & Mounting

Model Number: GM-HU37DW



Features

- Adds 7 USB 3.0 5Gbps Compliant Ports Clearly Labeled
- Includes 600W Surge Protection over each USB port and 15KV ESD
- Redundant 9-24V DC power input
- Wall and DIN Rail mount support
- Includes 3-wire terminal plug connector for wired power

Package Contents

- 3-Pin Terminal Block
- Power Supply
- USB Cable
- Hub
- DIN rail bracket
- Mounting Bracket
- Power Cable
- Screw Pack

Specifications

OVERVIEW

Model No	GM-HU37DW
Product Type	USB Hub
Compliance	CE FCC REACH RoHS
UPC	045079159938
Country of Origin	China
LED indicators	Port Status Power
Chipset	VL817-Q7S
Electrical Protections	Yes

PHYSICAL

Ship Weight (lbs)	1.49 lbs
Ship Weight (kg)	0.68 kg
Length	5.3 inches
Width	2.37 inches
Height	0.94 inches
Material	Steel
Color	Black
Mountable	Din-Rail Surface Mount

Specifications Cont.

CONNECTIONS	
USB Specification	USB 3.2 Gen 1
Upstream Port Type	USB 3.2G1 / 3.0 Type-B Female
Maximum Data Rate	5 Gbps
Downstream Port Count	7
Downstream Port Type	7x Type A USB 3.2 G1 / 3.0
Works as Standalone Charger	N - Requires Host to function
Can be Bus Powered	N - External Power Required
POWER	
Input Voltage	9 ~ 24V DC
Idle Power Draw	13mA @ 12V Terminal Power
Max Power Draw	36W
Max Per Port Draw	1A (5W)
Supported Charge Protocols	CDP
ENVIRONMENTAL	
Operating Temperature	0C ~ 40C
Storage Temperature	-20c ~ 50C
Operating Humidity	5% to 85% RH
OS SUPPORT	
Supported Operating Systems	OS independent - No software or drivers required
WARRANTY	
Warranty Period	1 Year
PRODUCT URL	
Mfg Page	https://www.gearmo.com/shop/usb-3-7-port-industrial-metal-hub-15kv-esd-protection-mounting/