

Technical Data Sheet Rev 06-260421

1 Port USB to Serial RS-232 Hub w/ FTDI Chipset & LED Indicators - Rugged Metal Housing Ideal for Mounting

Model Number: GM-FTDI1X-M



Features

- Adds 1 standard RS-232 serial port to your laptop, desktop, or other host system utilizing a high performance FTDI Chipset
- 25kV of protection from static electricity and surges to keep your connected equipment safe from damage.
- COM retention saves the assigned COM port number even after accidental disconnects.
- Surface mount or DIN-Rail mount this adapter with the included mounting brackets.
- Supported OS: Windows 11, 10, 8, 7, Linux, and MacOS.

Package Contents

- DIN rail bracket
- Hub
- Mounting Bracket
- Screw Pack
- USB Cable

Specifications

OVERVIEW

Model No	GM-FTDi1X-M	Product Type	Serial Adapter
Compliance	CE FCC REACH RoHS	UPC	045079161498
Country of Origin	China	LED indicators	Power TX/RX
Chipset	FTDI FT2232H	Electrical Protections	25kv

PHYSICAL

Ship Weight (lbs)	0.32 lbs	Ship Weight (kg)	0.15 kg
Item Weight	0.324 lbs	Length	2.56 inches
Width	1.97 inches	Height	0.98 inches
Material	Steel	Color	Black
Mountable	Din-Rail Mount Surface Mount Wall Mount		

Specifications Cont.**CONNECTIONS**

USB Specification	USB 2.0
Connector(s)	DB9 Male w/ Nuts USB 2.0 Type B Female
Maximum Data Rate	921.6kbps

SERIAL SPECS

Maximum Data Rate	921.6 Kbps
Serial Modes	RS232
RS232 Signals	TxD, RxD, RTS, CTS, DSR, DTR, DCD, RI, GND

ENVIRONMENTAL

Operating Temperature	0C ~ 50C
Storage Temperature	-20C ~ 70C
Operating Humidity	15 ~ 85% RH

OS SUPPORT

Supported Operating Systems	Linux OSX 10 Windows 11 Windows 10 Windows 8 Windows 7
------------------------------------	--

WARRANTY

Warranty Period	1 Year
------------------------	--------

PRODUCT URL

Product Page	https://www.gearmo.com/shop/1-port-usb-to-serial-rs-232-hub-w-ftdi-chipset-led-indicators-rugged-metal-housing-ideal-for-mounting/
---------------------	---