

Technical Data Sheet Rev 06-260401

10-Port USB Type-A 3.2 Gen 1 Hub - 15kV ESD Protection

Model Number: GM-HU310A



Features

- Expand your peripheral capabilities with 10 USB Type-A ports.
- Keep connections safe with extensive ESD surge protection. Housed in a steel metal chassis, this hub is ready to tackle harsh industrial environments.
- Wide input voltage range of 9 ~24V DC. Power either via DC Barrel or through a 3-Pin Terminal Block (power supply not included).
- Fast data transfer rates with USB Type-A ports offering 5Gbps
- Mounting options include Surface, Wall, and DIN-Rail

Package Contents

- 3-Pin Terminal Block
- DIN rail bracket
- Hub
- Mounting Bracket
- Screw Pack
- USB Cable
- User Manual

Specifications

OVERVIEW

Model No	GM-HU310A	Product Type	USB Hub
Compliance	CE FCC REACH RoHS	UPC	045079164390
Country of Origin	China	LED indicators	Power
Chipset	VL817-Q7S	Electrical Protections	15KV

PHYSICAL

Ship Weight (lbs)	1.1 lbs	Ship Weight (kg)	0.5 kg
Item Weight	0.725 lbs	Length	6.3 inches
Width	2.66 inches	Height	0.99 inches
Material	Steel	Color	Black
Mountable	Din-Rail Mount Surface Mount Wall Mount		

Specifications Cont.

CONNECTIONS

USB Specification	USB 3.2 Gen 1
Upstream Port Type	USB 3.2G1 / 3.0 Type-B Female
Maximum Data Rate	5 Gbps
Downstream Port Count	10
Downstream Port Type	10x Type A USB 3.2 G1 / 3.0
Works as Standalone Charger	Y - Can be used without Host
Can be Bus Powered	-

POWER

Input Voltage	9 ~ 24V DC
Power Connector	DC barrel, 2.1 ID x 5.5 OD, Center Pin Positive
Max Power Draw	50W
Max Per Port Draw	5W (1A)

ENVIRONMENTAL

Operating Temperature	0C ~ 50C
Storage Temperature	-20C ~ 70C
Operating Humidity	15 ~ 85% RH

OS SUPPORT

Supported Operating Systems	Linux OSX 10 Windows 11 Windows 10 Windows 8 Windows 7 Windows Vista
------------------------------------	--

WARRANTY

Warranty Period	1 Year
------------------------	--------

PRODUCT URL

Product Page	https://www.gearmo.com/shop/10-port-usb-3-2-gen-1-hub-w-esd-protection/
---------------------	---