

Technical Data Sheet Rev 06-260407

USB 3.0 4 Port Industrial Din Rail Mount Hub w/Power Adapter

Model Number: GM-HU34-PS



Features

- Adds 4 USB 3.0 Super-Speed Ports
- Supports UASP function (with Windows 8 native USB 3.0 Host driver only)
- Redundant 9VDC to 24VDC power input
- Over-current detection and protection circuit design. Includes 15kV ESD protection.
- Includes surface mounting brackets and DIN rail clip for mounting options

Package Contents

- 3-Pin Terminal Block
- DIN rail bracket
- Hub
- Mounting Bracket
- Power Supply
- Screw Pack
- USB Cable

Specifications

OVERVIEW

Model No	GM-HU34-PS	Product Type	USB Hub
Compliance	CE FCC REACH RoHS	UPC	045079158474
Country of Origin	China	LED indicators	Power
Chipset	VL811-Q8P	Electrical Protections	15KV

PHYSICAL

Ship Weight (lbs)	1.57 lbs	Ship Weight (kg)	0.71 kg
Item Weight	1.0625 lbs	Length	5.47 inches
Width	2.69 inches	Height	0.98 inches
Material	Steel	Color	Black
Mountable	Din-Rail Mount Surface Mount Wall Mount		

Specifications Cont.

CONNECTIONS

USB Specification	USB 3.2 Gen 1
Upstream Port Type	USB 3.2G1 / 3.0 Type-B Female
Maximum Data Rate	5 Gbps
Downstream Port Count	4
Downstream Port Type	4x Type A USB 3.2 G1 / 3.0
Works as Standalone Charger	N - Requires Host to function
Can be Bus Powered	N - External Power Required

POWER

Input Voltage	9 ~ 24V DC
Idle Power Draw	13mA @ 12V Terminal Power
Max Power Draw	24W
Max Per Port Draw	1A (5W)
Supported Charge Protocols	CDP

OS SUPPORT

Supported Operating Systems	OS independent - No software or drivers required
------------------------------------	--

WARRANTY

Warranty Period	1 Year
------------------------	--------

PRODUCT URL

Product Page	https://www.gearmo.com/shop/usb-3-4-port-rugged-industrial-din-rail-mount-hub-power-adapter/
---------------------	---