

Technical Data Sheet Rev 06-260403

USB 3.0 4 Port Industrial Metal Hub w/15KV ESD Protection

Model Number: GM-HU34DW



Features

- Compliant with Universal Serial Bus 3.0 Specifications
- Power input 15kv ESD surge protection to 600W for each port
- Wall and DIN Rail mount support
- Rugged Industrial-grade Chassis for Harsh Environments
- 15kv ESD, 600w Surge supression

Package Contents

- DIN rail bracket
- Hub
- Mounting Bracket
- Power Supply
- USB Cable

Specifications

OVERVIEW

Model No	GM-HU34DW	Product Type	USB Hub
Compliance	CE FCC REACH RoHS	UPC	045079159822
Country of Origin	China	LED indicators	Port Status Power
Chipset	VL813	Electrical Protections	15KV

PHYSICAL

Ship Weight (lbs)	1.26 lbs	Ship Weight (kg)	0.57 kg
Item Weight	0.46 lbs	Length	4.57 inches
Width	2.09 inches	Height	1.02 inches
Material	Steel	Color	Black
Mountable	Din-Rail Surface Mount		

Specifications Cont.

CONNECTIONS

USB Specification	USB 3.2 Gen 1
Upstream Port Type	USB 3.2G1 / 3.0 Type-B Female
Maximum Data Rate	5 Gbps
Downstream Port Count	4
Downstream Port Type	4x Type A USB 3.2 G1 / 3.0
Works as Standalone Charger	N - Requires Host to function
Can be Bus Powered	N - External Power Required

POWER

Input Voltage	9 ~ 24V DC
Idle Power Draw	13 mA @12V DC
Max Power Draw	24W
Max Per Port Draw	1.5A
Supported Charge Protocols	CDP DCP SDP

ENVIRONMENTAL

Operating Temperature	0C ~ 55C
Storage Temperature	-20C ~ 75C
Operating Humidity	5% to 95% RH

OS SUPPORT

Supported Operating Systems	Linux OSX 10 Windows 11 Windows 10 Windows 8 Windows 7 Windows Vista Windows XP
------------------------------------	---

WARRANTY

Warranty Period	1 Year
------------------------	--------

PRODUCT URL

Product Page	https://www.gearmo.com/shop/usb-3-4-port-industrial-metal-hub-15kv-esd-protection/
---------------------	---