

Technical Data Sheet Rev 06-260403

4-Port USB 3.0 Rugged Industrial DIN Rail & Surface Mount Hub

Model Number: GM-HU34



Features

- Compliant with USB 3.0 Standards
- Adds 4 additional USB High Speed ports
- Supplies independent over-current detection and circuit protection to all ports
- Includes both DIN-Rail and mounting brackets for multiple mounting options
- Constructed with an Industrial designed rugged metal chassis

Package Contents

- 3-Pin Terminal Block
- DIN rail bracket
- Hub
- Mounting Bracket
- Screw Pack
- USB Cable

Specifications

OVERVIEW

Model No	GM-HU34	Product Type	USB Hub
Compliance	CE FCC REACH RoHS	UPC	736983901088
Country of Origin	China	LED indicators	None or N/A
Chipset	VL811+	Electrical Protections	15KV

PHYSICAL

Ship Weight (lbs)	0.5 lbs	Ship Weight (kg)	0.23 kg
Item Weight	0.5 lbs	Length	5.47 inches
Width	2.69 inches	Height	0.98 inches
Material	Steel	Color	Black
Mountable	Din-Rail Surface Mount		

Specifications Cont.

CONNECTIONS

USB Specification	USB 3.2 Gen 1
Upstream Port Type	USB 3.2G1 / 3.0 Type-B Female
Maximum Data Rate	5 Gbps
Downstream Port Count	4
Downstream Port Type	4x Type A USB 3.2 G1 / 3.0
Works as Standalone Charger	N - Requires Host to function
Can be Bus Powered	N - External Power Required

POWER

Input Voltage	9 ~ 24V DC
Power Connector	DC barrel, 2.1 ID x 5.5 OD, Center Pin Positive
Idle Power Draw	13mA @ 12V Terminal Power
Max Power Draw	24W
Max Per Port Draw	1A (5W)
Supported Charge Protocols	CDP DCP SDP

OS SUPPORT

Supported Operating Systems	Linux OSX 10 Windows 11 Windows 10 Windows 8 Windows 7 Windows Vista Windows XP
------------------------------------	---

WARRANTY

Warranty Period	1 Year
------------------------	--------

PRODUCT URL

Product Page	https://www.gearmo.com/shop/4-port-usb3-rugged-industrial-din-rail-mount-hub/
---------------------	---