

Technical Data Sheet Rev 06-260715

USB 3.0 7 Port Industrial Metal Hub w/15KV ESD Protection & Mounting

Model Number: GM-HU37DW



Features

- Adds 7 USB 3.0 5Gbps Compliant Ports Clearly Labeled
- Includes 600W Surge Protection over each USB port and 15KV ESD
- Redundant 9-24V DC power input
- Wall and DIN Rail mount support
- Includes 3-wire terminal plug connector for wired power

Package Contents

- 3-Pin Terminal Block
- Power Supply
- USB Cable
- Hub
- DIN rail bracket
- Mounting Bracket
- Power Cable
- Screw Pack

Specifications

OVERVIEW

Model No	GM-HU37DW	Product Type	USB Hub
Compliance	CE REACH RoHS	UPC	045079159938
Country of Origin	China	LED indicators	Port Status Power
Chipset	VL813	Electrical Protections	Yes

PHYSICAL

Ship Weight (lbs)	1.49 lbs	Ship Weight (kg)	0.68 kg
Item Weight	0.6625 lbs	Length	5.3 inches
Width	2.37 inches	Height	0.94 inches
Material	Steel	Color	Black
Mountable	Din-Rail Surface Mount		

Specifications Cont.

CONNECTIONS

USB Specification	USB 3.2 Gen 1
Upstream Port Type	USB 3.2G1 / 3.0 Type-B Female
Maximum Data Rate	5 Gbps
Downstream Port Count	7
Downstream Port Type	7x Type A USB 3.2 G1 / 3.0
Works as Standalone Charger	N - Requires Host to function
Can be Bus Powered	N - External Power Required

POWER

Input Voltage	9 ~ 24V DC
Power Connector	Phoenix 3-pin
Idle Power Draw	13mA @ 12V Terminal Power
Max Power Draw	37.5W
Max Per Port Draw	900mA (4.5W)
Supported Charge Protocols	SDP

ENVIRONMENTAL

Operating Temperature	0C ~ 40C
Storage Temperature	-20C ~ 50C
Operating Humidity	5% to 85% RH

OS SUPPORT

Supported Operating Systems	Linux OSX 10 Windows 11 Windows 10 Windows 8 Windows 7 Windows Vista Windows XP
------------------------------------	---

WARRANTY

Warranty Period	1 Year
------------------------	--------

PRODUCT URL

Product Page	https://www.gearmo.com/shop/usb-3-7-port-industrial-metal-hub-15kv-esd-protection-mounting/
---------------------	---